

TITLE: MOTOR DATA. ISOLATING RANGE S2-30 MIN DUTY CYCLE, AC 3-500V/50Hz THREE PHASE
MODELS: CK, CKA, CKC

Actuator model		Output speed (rpm)	Max. tripping torque (N.m)	Nominal torque (N.m)	Motor speed (rpm)	Nominal Power (kW)	Nominal current (A)	Power at max tripping torque (kW)	Current at max tripping torque (A)	Locked rot. current (A)	Power factor (nominal) cos φ	Overcurrent prot. device setting (A)	Contactors	Thyristor
CK30	009	9	30	10	720	0,29	0,58	0,29	0,58	1,05	0,64	0,58	Standard	OPTIONAL
	012	12			720	0,29	0,58	0,29	0,58	1,05	0,64	0,58	Standard	OPTIONAL
	018	18			1440	0,21	0,42	0,25	0,50	1,26	0,74	0,50	Standard	OPTIONAL
	024	24			1440	0,27	0,55	0,30	0,60	1,71	0,62	0,60	Standard	OPTIONAL
	036	36			1440	0,30	0,60	0,34	0,68	1,97	0,57	0,68	Standard	OPTIONAL
	048	48			1440	0,34	0,67	0,38	0,75	1,96	0,73	0,75	Standard	OPTIONAL
	072	72			1440	0,39	0,78	0,46	0,92	2,84	0,50	0,92	Standard	OPTIONAL
	096	96			1440	0,46	0,92	0,57	1,14	3,38	0,60	1,14	Standard	OPTIONAL
	144	144			2880	0,57	1,13	0,96	1,91	3,84	0,90	1,91	Standard	OPTIONAL
	192	192	25	8,3	2880	0,31	0,61	0,83	1,66	3,75	0,60	1,66	Standard	OPTIONAL
CK60	009	9	60	20	720	0,39	0,77	0,39	0,77	1,48	0,73	0,77	Standard	OPTIONAL
	012	12			720	0,38	0,76	0,38	0,76	1,52	0,60	0,76	Standard	OPTIONAL
	018	18			1440	0,40	0,81	0,45	0,90	2,79	0,60	0,90	Standard	OPTIONAL
	024	24			1440	0,39	0,78	0,62	1,23	3,14	0,61	1,23	Standard	OPTIONAL
	036	36			1440	0,44	0,89	0,55	1,09	3,34	0,54	1,09	Standard	OPTIONAL
	048	48			1440	0,49	0,98	0,68	1,35	3,65	0,50	1,35	Standard	OPTIONAL
	072	72			1440	0,84	1,69	1,00	2,01	5,66	0,55	2,01	Standard	OPTIONAL
	096	96			1440	0,82	1,63	1,02	2,05	6,02	0,55	2,05	Standard	OPTIONAL
	144	144			2880	0,47	0,94	0,47	0,94	11,25	0,59	0,94	Standard	OPTIONAL
	192	192	50	16,7	2880	0,42	0,83	0,42	0,83	11,32	0,37	0,83	Standard	OPTIONAL
CK120	009	9	120	40	720	1,13	2,25	1,99	3,98	15,21	0,56	3,98	Standard	OPTIONAL
	012	12			720	1,13	2,25	1,99	3,98	15,21	0,56	3,98	Standard	OPTIONAL
	018	18			1440	0,62	1,23	0,90	1,80	4,57	0,55	1,80	Standard	OPTIONAL
	024	24			1440	0,67	1,33	0,67	1,33	6,37	0,42	1,33	Standard	OPTIONAL
	036	36			1440	0,67	1,33	1,02	2,03	6,63	0,28	2,03	Standard	OPTIONAL
	048	48			1440	0,70	1,40	1,00	2,00	6,50	0,46	2,00	Standard	OPTIONAL
	072	72			1440	0,70	1,40	1,48	2,97	6,57	0,57	2,97	Standard	OPTIONAL
	096	96			1440	0,75	1,50	2,23	4,47	12,67	0,65	4,47	Standard	OPTIONAL
	144	144			2880	1,55	3,10	2,25	4,50	19,43	0,56	4,50	Standard	OPTIONAL
	192	192	100	33,3	2880	1,98	3,97	2,63	5,27	19,73	0,81	5,27	Standard	OPTIONAL
CK250	009	9	250	83,3	720	1,13	2,25	1,99	3,98	15,21	0,56	3,98	Standard	OPTIONAL
	012	12			720	0,75	1,50	0,75	1,50	4,90	0,35	1,50	Standard	OPTIONAL
	018	18			1440	0,80	1,60	1,12	2,23	9,47	0,46	2,23	Standard	OPTIONAL
	024	24			1440	0,83	1,67	1,23	2,47	9,30	0,49	2,47	Standard	OPTIONAL
	036	36			1440	1,10	2,20	1,10	2,20	13,00	0,22	2,20	Standard	OPTIONAL
	048	48			1440	1,10	2,20	1,10	2,20	12,93	0,31	2,20	Standard	OPTIONAL
	072	72			1440	1,82	3,63	2,43	4,87	24,73	0,41	4,87	Standard	OPTIONAL
	096	96			1440	1,38	2,77	2,77	5,53	18,27	0,60	5,53	Standard	N/A
	144	144			2880	1,57	3,13	1,57	3,13	35,07	0,53	3,13	Standard	N/A
	192	192	200	66,7	2880	1,47	2,93	1,47	2,93	35,07	0,44	2,93	Standard	N/A
CK500	009	9	500	166,7	720	1,33	2,67	1,33	2,67	8,60	0,27	2,67	Standard	OPTIONAL
	012	12			720	1,35	2,70	1,35	2,70	8,70	0,26	2,70	Standard	OPTIONAL
	018	18			1440	1,22	2,43	1,95	3,90	18,53	0,33	3,90	Standard	OPTIONAL
	024	24			1440	1,13	2,27	2,08	4,17	12,60	0,57	4,17	Standard	OPTIONAL
	036	36			1440	1,40	2,80	2,50	5,00	18,23	0,59	5,00	Standard	OPTIONAL
	048	48			1440	1,58	3,17	3,38	6,77	18,03	0,70	6,77	Standard	OPTIONAL
	072	72			1440	3,19	5,79	4,45	8,90	26,63	0,62	8,90	Standard	OPTIONAL
	096	96			1440	2,40	4,80	6,58	13,17	38,37	0,70	13,17	Large	N/A
	144	144			2880	2,03	4,07	2,03	4,07	62,87	0,11	4,07	Standard	N/A
	192	192	400	133,3	2880	2,40	4,80	2,40	4,80	62,53	0,44	4,80	Standard	N/A

AC 3-500V/50Hz asynchronous motors. Short-time duty S2 - 30 min, based on nominal torque at 40°C ambient temperature. Insulation class H. Motors are suitable for 60 starts/hour operation.

Motor data is approximate, due to manufacturing tolerances, there may be deviations from the stated values. Permissible variation of the mains voltage: $\pm 10\%$. Permissible variation of the mains frequency: $\pm 5\%$ Electric motors are provided with thermoswitches to protect the motor windings against overheating. Thermoswitches are embedded in the motor windings: If those thermoswitches are not connected, or by-passed, in the control circuit actuators will NO longer comply with the essential safety requirements, in that case Rotork warranty will lapse. CKC electric actuators with centronik-atronik unit, see datasheet for centronik-atronik unit current consumption.